



| Part (code) | Qty. | T | W | L | Materials | Rgh. ✓ | Fin. ✓ | Notes |
|-------------------------|------|-------|-------|--------|-----------|--------|--------|---|
| Side (S) | 2 | 7/8 | 9 1/4 | 32 1/2 | P | | | Blank size given; Cut shape from pattern. |
| Arm (A) | 2 | 3/4 | 6 1/2 | 27 | P | | | Blank size given; Cut shape from pattern. |
| Temporary brace | 1 | 1 3/8 | 5 1/4 | 14 1/4 | CL | | | Bevel ends to 7°. |
| Back support slat (BSS) | 1 | 3/4 | 2 | 16 1/2 | P | | | Miter ends to 6°. |
| Main slat blank (MS) | 7 | 3/4 | 2 | 21 1/4 | P | | | Will be individually mitered to length. |
| Nose slat (NS) | 4 | 3/4 | 1 1/4 | CTF | P | | | Bevel edges to 18°. |
| Leg front blank (LF) | 2 | 3/4 | 4 1/2 | 22 3/4 | P | | | Bevel bottom end to 12° and top end to 10-1/2°. |
| Leg side blank (LS) | 2 | 3/4 | 3 7/8 | 23 3/4 | P | | | Miter ends to match bevels on leg fronts. |
| Spacer block blank (SB) | 2 | 1 1/4 | 4 1/2 | 5 1/2 | P | | | |
| Back splat (BS) | 2 | 3/4 | 5 3/4 | 42 | P | | | |
| Back connectors (BC) | 2 | 1 | 1 1/4 | 10 1/2 | P | | | Miter ends at 30° |
| Back blocks (BB) | 2 | 1 1/2 | 2 | 7 | P | | | Bevel top ends to 11° and forward faces to 10°. |
| Arm support (AS) | 1 | 1 1/2 | 1 1/2 | 20 | P | | | Cut to length after installing arms. |

Materials: **P**=Thermally-treated Poplar; **CL**=Construction Lumber

CTF=Cut to fit.